



# 2X-833

## WALK THROUGH METAL DETECTOR

### SYSTEM APPLICATIONS

- > Ports
- > Airports
- > Train stations
- > Hospitals
- > Hotels
- > Commercial governments
- > Banks

The 2X-833 is a leader in its class and offers security operators a reliable system for use in various operational environments. Ease of use and installation make the 2X-833 WTMD the perfect choice for any security check point.

- > The independent zone indicator lights on both sides of the of each panel provide the means to identify the height, left and right locations for one or more objects passing through the archway
- > 7" colour LCD touch sensitive screen, infrared remote control. LED and adjustable audible sound alarms. LED indicators on both sides to indicate the position of the threat.
- > 33 detection zones, simultaneous alarm from multiple zones, each zone is adjustable with 999 sensitivity levels
- > Analyses targets across a broad range of frequencies for greater accuracy and reduced alarms
- > Omnidirectional detection, transmitters on each side to allow scanning from both sides
- > Automatic passenger counts an alarm times, can be customised to 36 zones
- > 100 frequencies options for positioning multiple units can be installed within 400mm of each other. 30 pre-set programs for various security application
- > Smooth, efficient traffic flow with easy to view, eye level indicators with wait and proceed symbols on each side of the archway



## TECHNICAL DATA

Zones	33 Programmable zones. Can be customised to 36
Control unit	7" LCD colour screen touch pad, infra-red remote control and tamper alarm
Diagnostics	Complete and automatic
Sensitivity	Sensitivity adjustable, each zone has 999 sensitivity levels
Alarms	Alarm volume range level 0-9 Alarm range level 1-9 PASS and ALARM count up to 99999
Battery option	4-8 hours backup available
Programmes	30 pre-set application for security
Weatherproofing	Meets IP55, IP65
Standard internal size	Width 700mm Height 2010mm Depth 500mm
Standard external size	Width 800mm Height 2200mm Depth 580mm
Temperatures	Operating -20C to +50C Storage -40C to 70c Humidity to 95% non-condensing
Power supply	AC85V-264V, 47.5-60Hz, >15W
Shipping weight	67kgs
Assembly	Easy 8 screws assembly and installation
Warranty	24 months limited parts/labour